



BUILT UP AREA DETAILS

EXISTING GROUND FLOOR	= 512.25 SQM
EXISTING FIRST FLOOR	= 514 SFT
EXISTING SECOND FLOOR	= 514 SFT
PROPOSED SECOND FLOOR	= 514 SFT
TOTAL AREA	= 1654.2 SFT
LADIES HOSTEL BUILDING	= 597.71 SQM
EXISTING GROUND FLOOR	= 643.4 SFT

TOTAL BUILT UP AREA

SHEET 1	COLLEGE BUILDING	= 1668.01 SQM
SHEET 2	COLLEGE CUM BOYS HOSTEL BUILDING	= 1536.75 SQM
	GIRLS HOSTEL BUILDING	= 597.71 SQM
	TOTAL AREA	= 3802.47 SQM

DOOR & WINDOW DETAILS

MARKS	BREATH	HEIGHT	TYPE
D	4'-0"	7'-0"	DOUBLE SHUTTER PANEL DOOR
D1	3'-0"	7'-0"	DOUBLE SHUTTER PANEL DOOR
GATE	6'-0"	7'-0"	COLLAPSIBLE GATE
D2	2'-6"	7'-0"	SINGLE SHUTTER FLUSH DOOR
W1	4'-0"	4'-0"	1/2 GLAZED DOUBLE LEAF PANEL SHUTTER
V	2'-6"	5'-0"	GLAZED

DESCRIPTION OF ITEMS

ITEM NO	DESCRIPTION
1.	CEMENT CONCRETE IN FOUNDATION, FLOOR WITH 1 1/2" (12 MM DOWN) STONE CHIPS
2.	BRICK WORK IN FOUNDATION, PLINTH, SUPER STRUCTURE WITH 14 CLASS BRICK AND CEMENT MORTAR
3.	5" AND 3" BRICK WORK IN PARTITION WALL, RAFT, ETC. WITH 14 CLASS BRICK AND CEMENT MORTAR WITH H.B. NETTING EVERY SECOND LAYER
4.	ALL R.C.C. WORKS IN ROOF, LINTEL, BEAM, COLUMN, STR AIR ETC. WITH 7/8" (20 MM DOWN) APPROVED QUALITY STONE CHIPS & STEEL MINIMUM GRADE T-45 TMT BAR
5.	PLASTER TO ALL WITH CEMENT MORTAR 15 M.M. AND 20 M.M. THICK
6.	PLASTER TO CEILING AND CONCRETE SURFACE WITH CEMENT MORTAR 10MM THICK
7.	ARTIFICIAL STONE IN FLOOR WITH CEMENT CONCRETE 1/2" DOWN STONE CHIPS WITH NEAT CEMENT AT TOP
8.	DAMP PROOF COURSE WITH 1/2" DOWN STONE CHIPS ADDED WITH WATER PROOFING ADMIXTURE

SIGNATURE OF AUTHORITY

SAJAL KR. BHANDARY

DRAWN BY: [Signature]

SHEET NO. 02-02

TOTAL SHEET NO. 02

(Licence no: P.M.-7659)

MOB :- 993392120, 8436942307

email: sajal.bhandary@rediffmail.com



